


Flex Cut-Off Wheels

Resin Bonded Abrasives

Metal Cut-off Wheels – A30 S BF

Application Area: Used for cutting operation of iron, steel and castings which have moderate hardness.



FLAT DPC.

DIMENSIONS (mm)	SPECIFICATION	PERIPHERAL SPEED	R.P.M	BOX UNITS
100 x 3 x 16	A 30 S BF	80 m/s	15300	25
115 x 3 x 22.23	A 30 S BF	80 m/s	13300	25
125 x 3 x 22.23	A 30 S BF	80 m/s	12250	25
180 x 3 x 22.23	A 30 S BF	80 m/s	8500	25
230 x 3 x 22.23	A 30 S BF	80 m/s	6650	25

- Regular aluminium oxide
- For general applications
- Faster cutting
- Long life
- High cutting performance

Inox Cut-off Wheels – 20A 30 P BF / E20A 60 S BF / E20A 46 S BF

Application Area: Used for cutting operation of low and high alloyed stainless steel materials, plates and sheets.



FLAT DPC.

DIMENSIONS (mm)	SPECIFICATION	PERIPHERAL SPEED	R.P.M	BOX UNITS
115 x 3 x 22.23	20A 30 P BF	80 m/s	13300	25
125 x 3 x 22.23	20A 30 P BF	80 m/s	12250	25
180 x 3 x 22.23	20A 30 P BF	80 m/s	8500	25
230 x 3 x 22.23	20A 30 P BF	80 m/s	6650	25

FLAT

THINLINE - E20A 60 S BF / E20A 46 S BF

DIMENSIONS (mm)	SPECIFICATION	PERIPHERAL SPEED	R.P.M	BOX UNITS
115 x 1 x 22.23	E20A 60 S BF	80 m/s	13300	50
115 x 1.6 x 22.23	E20A 60 S BF	80 m/s	13300	50
125 x 1 x 22.23	E20A 60 S BF	80 m/s	12250	50
125 x 1.6 x 22.23	E20A 60 S BF	80 m/s	12250	50
180 x 1.9 x 22.23	E20A 46 S BF	80 m/s	8500	25
230 x 1.9 x 22.23	E20A 46 S BF	80 m/s	6650	25

- Semi-friable aluminium oxide
- Faster cutting
- Cool cutting
- Long life
- Excellent quality
- THINLINE products are Fe, S and Cl free